



**4" Clamped Butterfly Valve** - left hand operated with TIR to handle and padlock facility. Contact parts manufactured in 316 stainless steel with Flexityt main seal.

**Options** - lockable handle. "Congealing cargo" version with semi-spherical closure plate. Version with high temperature seals. Pneumatic actuator available.

Arrange of 2" and 3" clamped valves is available.

## Specification

Weight	4 Kg
Design Pressure (MAWP)	6 Bar (87 PSI)
Test Pressure	10 Bar (145 PSI)
Design Temperature Range	-40°C to 250°C (-40°F to 482°F)

Above information varies according to specification.  
Design approval by Lloyds Register of Shipping.  
Approved to BS EN14432.

## Range

Part No.	Description
468/7250B	Left hand standard butterfly valve
468/7200BPN	Fitted with pneumatic actuator
468/725HTB	Fitted with high temperature seals
468/7260SHB	Steam heated, semi-spherical closure plate

## Associated Parts

Associated Parts	Part No.
CNAF/PTFE inlet gasket	5005-468
CNAF/PTFE outlet gasket	5005-469
Bolting kit (8 x bolts, nuts, washers)	468/1100
4" BSP outlet flange	468/8047
4" BSP blank cap with PTFE washer	10304PSC
4" NPT outlet flange	468/8049
4" NPT blank cap with PTFE washer	425/4000

## Fitting Details

Part number : 468/7250B

