



Halar Lined 4" to 3" Hydraulic Highlift Footvalve - inlet flange drilled 8 x 14mm holes equi-spaced on a 184mm PCD (4" TTMA). Outlet flange drilled 8 x 11mm holes equi-spaced on a 124mm PCD (3" TTMA). Hydraulic actuator with 1/8" NPT connections. Valve manufactured in 304/316 stainless steel fitted with a Viton main seal. All parts in contact with the cargo lined with Halar and lifting rod encased in PTFE bellows.

Options - other Halar lined products available : 3" 45° Footvalve; 3" Ball valve; 2" Ball valve.

Specification

Weight	15 Kg
Design Pressure (MAWP)	4 Bar (58.0 PSI)
Test Pressure	6 Bar (87.0 PSI)
Design Temperature	-20°C to +100°C (-4°F to +212°F)

Halar Lined Product Range

Part No.	Description
82L/1000	Halar lined 3" 45° Footvalve
370/L100	Halar lined 2" Ball valve
360/L050X	Halar lined 3" Ball valve

Associated Parts

Part Number	Description
299/0102	4" TTMA Tank pad
5005-441	Inlet gasket - CNAF/Teflon envelope
5005-445	Outlet gasket - CNAF/Teflon envelope

Fitting Details

Part Number : 299/L710GS

