

TW Couplings

TW Couplings are produced to EN 14420-6:2004 and are available in 50mm (2"), 80mm (3") and 100mm (4").



Male Connection

Description	Part No.
VK50 coupler in stainless steel	90/TWVK50SS
VK80 coupler in stainless steel	90/TWVK80SS
VK100 coupler in stainless steel	90/TWVK100SS

Caps

Description	Part No.
MB50 cap in stainless steel	90/TWMB50SS
MB80 cap in stainless steel	90/TWMB80SS
MB100 cap in stainless steel	90/TWMB100SS

Associated Parts

Main gasket to suit female coupler.

Description	Part No.
50mm CSM gasket	5005-TWMK50HYP
80mm CSM gasket	5005-TWMK80HYP
100mm CSM gasket	5005-TWMK100HYP
50mm natural black rubber gasket	5005-TWMK50NBR
80mm natural black rubber gasket	5005-TWMK80NBR
100mm natural black rubber gasket	5005-TWMK100NBR

Thread seal.

Description	Part No.
50mm PTFE seal	5005-TW50PTFE
80mm PTFE seal	5005-TW80PTFE
100mm PTFE seal	5005-TW100PTFE

Female Connection

Description	Part No.
MK50 coupler in stainless steel	90/TWMK50SS
MK80 coupler in stainless steel	90/TWMK80SS
MK100 coupler in stainless steel	90/TWMK100SS

Plugs

Description	Part No.
VB50 plug in stainless steel	90/TWVB50SS
VB80 plug in stainless steel	90/TWVB80SS
VB100 plug in stainless steel	90/TWVB100SS